

CLAIMS

1. An ultrasonic diagnostic apparatus for delay-controlling the ultrasonic wave beams of a plurality of ultrasonic transducer elements
5 linearly arranged in a horizontal direction to a specimen, characterized by:

means for deriving the distance from each of said plurality of ultrasonic transducer elements to said convergence positions with from a hyperbolic function wherein the gradient "a" of an asymptote is $0 < |a|$
10 < 1 , with the positions in a horizontal direction of said plurality of ultrasonic transducer elements as the variable; and

means for generating the driving pulse of each of said plurality of ultrasonic transducer elements delayed in accordance to said derived distances.

15

2. An ultrasonic diagnostic apparatus for delay-controlling the ultrasonic wave beams of a plurality of ultrasonic transducer elements arranged on a convex surface in a horizontal direction to a specimen, characterized by:

20 means for deriving the distance from each of said plurality of ultrasonic transducer elements to said convergence positions from the sum of a hyperbolic function wherein the gradient "a" of an asymptote is $0 < |a| < 1$, with the positions in a horizontal direction of said plurality of ultrasonic transducer elements as the variable, and the distance from
25 each of said ultrasonic transducer elements and a reference line to which

the ultrasonic transducer element in the center contacts on the convex surface; and

means for generating the driving pulse of each of the said plurality of ultrasonic transducer elements delayed in accordance to said derived
5 distances.